

- Made from the flame resistant fibre, it is a configurable, environmental friendly, and flame resistant product
- Flexibility , washable many times. Large dust holding capacity, long service life
- Gradual structure, the fiber density increases gradually toward the pure air
- It can fully substitute for similar imported products
- Conform to European, Chinese and Japanese classifications for the nonflammablilith(eg:DIN 53438-F1,GB5454-1977B1,JCAC NO.11A-2003)



■ 用途 Using

- 用于各种空气过滤设备的预过滤，用于各种工业用途，如防治污染，公共建设，空调业，电子业，制药业，食品业等
It used as the pre-filter for the air handling equipment. Applied to many industry such as pollution controlling, public sonstruction, air-condition, electronic, pharmacy, food and so on



■ 性能参数 Specification

Type 型号	Filter Class 过滤等级	Standard Dimensions (m) 标准尺寸	Thickness (mm) 厚度	flame resistant 阻燃性 ○ X	oxygen index 氧指数 LOI	Washable 可清洗 ⊗	Weight 克重 (g/m ²)	Average Arrestance (%) 平均计重效率	Media velocity (m/s) 风速	Initial pressure drop (Pa) 初阻力	Recommended final prssure drop(Pa) 建议终阻力	Dust holding capacity (g/m ²) 容尘量	Thermal Stability (°C) 持续温度
GS-150	G1	1.6*30	8 ±2	○	26	○	150 ± 15	62	2.5	30	150	380	80
GS-300	G2	1.6*30	10 ±2	○	26	○	200 ±20	70	2.5	54	150	600	80
GS-400	G2	1.6*20	14 ±2	○	28	○	300 ±25	76	2.5	64	200	600	80
GS-600	G3	1.6*20	20 ±2	○	30	○	400 ±30	82	2.5	93	250	—	80

- 注：可根据客户要求定做其它规格尺寸 **Remark:**Wide variety of sizes.according to the customer's requirement